

Ronez Flow Product Information



Ronez Flow is a range of highly specialised self compacting concrete formulations, each presenting significant advantages over the equivalent traditional concrete.

Designed to provide a highly fluid consistency and minimal energy consumption in use. Ronez Flow is based on carefully selected and controlled binders and admixtures in conjunction with aggregates selected in accordance with the proposed end use.

Ronez Flow offers contractors and specifiers a high performance, secure fast track solution to many of the more challenging aspects of construction.

Ronez Flow when correctly specified and placed will deliver:

- High quality finishes - Ronez Flow is capable of delivering the finest surface finish and detail in areas of difficult access, complex formwork or very heavily reinforced sections. The mix design concept applied to products in this range ensures each product is robust under all normal site conditions
- Reduced or eliminated remedial work
- Reduced labour requirements - labour friendly concrete, the simplicity of placing together with the elimination of compaction and in many instances only very minor finishing effort will ensure a project achieves savings in terms of time and cost
- Ronez Flow is easier to place and finish than conventional concrete, and is available in standard strengths up to 40 N/mm². Higher grades are possible.
- Improved output in precast environments
- Reduced impact on the environment - noise impact of the construction operation is greatly reduced, concrete pumps run more quietly and the need for all forms of vibration is eliminated. The use of power floating is eliminated

Ronez Flow

Product Information

- Reduces placing and finishing time - the enhanced rate of placing that can be achieved using Ronez Flow allows the scheduling of larger pours or a reduction in working hours required. The elimination of late working or overtime costs can significantly benefit the environment through these actions
- The potential to eliminate late working and finishing is a significant reduction in the environmental impact of construction
- Ronez Flow preparation allows the contractor to 'place and finish' concrete without the normal delay between placing and finishing operations.
- When used as a screed, can offer superior performance over traditional sand cement and flowing screed mixes
- Elimination of "vibration white finger" risk
- Ronez Flow can be tailored to the particular challenges of your contract
- Ronez Flow is compatible with flowing screed when used in association with underfloor heating systems

Applications

Ronez Flow may be utilised in all forms of construction in residential, transport infrastructure, office and administrative buildings as well as military engineering, hotels, schools and hospitals repair and refurbishment.

Manufacturing standard

Ronez Flow conforms to the requirements of European standard BS EN 206-1 and with the requirements of BS8500-1 and BS 8500-2 2006.

As with all Aggregate Industries' products Ronez Flow is manufactured under an independently monitored third party quality assurance scheme in accordance with ISO 9001, and with factory environmental compliance to ISO 14001.

Installation standard

The Ronez Flow range may be placed by any conventional method. Achieving the optimum finished surfaces may require discussion with our technical services department before construction begins. Successful placing has been achieved using pump, conventional skip and direct placement methods.

Curing

As with any concrete to achieve the desired properties it is essential to ensure correct and adequate curing.

Self compacting concrete has a high fines content and has a low tendency to bleed; this characteristic means the initial curing operations should begin as soon as practicable after finishing the surface to minimise the risk of premature drying and plastic shrinkage cracks. For larger pours the curing process must run consecutively to the finishing operation. The use of a correctly applied 90% efficiency curing membrane has been shown to be adequate. Curing should continue for a minimum of 7 days

Ronez Flow

Product Information

Typical performance and technical data

The engineering properties of Ronez Flow may be taken as being in all respects similar to conventional concrete and for design purposes should be assumed to be those stated in EN1992-1-1 table 3.1 .

Available in strength classes	C20 to C40 higher grades possible
-------------------------------	--------------------------------------

Flexural strength from	4 N/mm ²
------------------------	---------------------

Typical drying shrinkage	0.6%
--------------------------	------

Maximum laying thickness Ronez Flow H	75mm
--	------

The consistence class to be utilised is dependent upon the application, it will be discussed and agreed prior to supply.

COSHH data

Full COSHH data on Ronez concrete products is available on request.

Ronez Limited

Les Vardes Quarry, St Sampson
Guernsey GY2 4TF
Tel: +44 (0)1481 256426

sales@ronez.com

www.ronez.com

Ronez Limited

Momains Yard, Vale
Guernsey GY2 5TZ
Sales: +44 (0)1481 201300
Technical: +44 (0)1481 201312

Ronez Limited

La Route du Nord, St John
Jersey JE3 4AR
Tel: +44 (0)1534 867212
Technical: +44 (0)1534 867214



PART OF THE ISLANDS' FOUNDATIONS

The information contained within this publication was accurate at time of production. However, Ronez Limited reserves the right to introduce modifications or changes to detail at any time without notice. No charge is levied for this publication or advice therein, and accordingly the company, its employees and authorised agents can accept no liability whatsoever, either indirectly or directly arising from the use of its products in connection with any information or advice contained in this guide.

A SigmaRoc PLC Company.